(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 25 January 2001 (25.01.2001)

PCT

(10) International Publication Number WO 01/06087 A1

(51) International Patent Classification7: 33/127

E21B 33/12,

Inventors: TURLEY, Rocky, A.; 12010 Cypress Pl. Dr., Houston, TX 77065 (US). YUAN, Yusheng; 9219 Fordshire Drive, Houston, TX 77025 (US).

(74) Agents: RIDDLE, J., Albert et al.; Baker Hughes Incor-

(81) Designated States (national): AU, CA, GB, NO.

porated, Suite 1200, 3900 Essex Lane, Houston, TX 77040

(21) International Application Number: PCT/US00/19916

(22) International Filing Date:

19 July 2000 (19.07.2000)

(25) Filing Language:

English

(26) Publication Language:

(30) Priority Data: 60/144,508

19 July 1999 (19.07.1999) US


English

Published: With international search report.

(71) Applicant: BAKER HUGHES INCORPORATED [US/US]; Suite 1200, 3900 Essex Lane, Houston, TX 77027 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: EXTRUSION RESISTANT INFLATABLE TOOL



(57) Abstract: Extrusion resistant inflatable tool having a biaxially oriented woven material disposed about at least one elastomeric element of the inflatable tool and radially inwardly of a rib structure of the inflatable tool. The woven material prevents extrusion of the elastomeric element between individual ribs of the ribs structure during the inflation of the tool.

EXTRUSION RESISTANT INFLATABLE TOOL

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of an earlier filing date from U. S. Provisional Application Serial Number 60/144,508.

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to downhole oil field tools. More particularly, the invention relates to performance enhancing devices for inflatable elements.

Prior Art

Inflatable elements such as packers have been known and used in the hydrocarbon production industry for a substantial period of time. During this time they have been reliable and favored by oil well operators in many sealing operations. Prior art inflatable elements have however had difficulty with setting in noncylindrical boreholes. Noncylindrical boreholes include oval borcholes, unconsolidated boreholes, windows, etc. The problems of the prior art inflatable elements in noncylindrical boreholes has been that the rubber of the inflatable boot is extruded through the ribs of the element. This can cause severe damage to the rubber of the boot and to the ribs of the element and may result in failure of the device. Thus, the art is in need of a means to avoid extrusion of the rubber boot of the inflatable element through the rib portion of the inflatable element during inflation of a tool in a noncylindrical environment.

SUMMARY OF THE INVENTION

The above-identified drawbacks of the prior art are overcome or alleviated by the extrusion resistant inflatable tool of the invention.

In the invention, a biaxially woven sleeve is interposed between the boot/inner-tube and the ribs of a tool having otherwise conventional components. The sleeve is preferably constructed of carbon fiber, aramid fiber, liber glass or suitable alternative fiber which

provides a bridge between the ribs of the inflatable tool as the element expands into the noncylindrical environment. The existence of the biaxially woven sleeve in an annular area outside the boot and inside the ribs of the element prevents the boot from being extruded through the ribs when they open excessively during expansion into a noncylindrical borehole environment. The sleeve further prevents excessive bending of the ribs which would otherwise create difficulties in removing the tool from the downhole environment.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings wherein like elements are numbered alike in the several FIGURES:

FIGURE 1 is a schematic cross section of the device of the invention illustrating the position of the extrusion resistant biaxially woven sleeve;

FIGURE 2 is a view of the sleeve itself illustrating the pattern thereof;

FIGURE 3 is an illustration of the sleeve disposed around the rubber boot; and

FIGURE 4 is an illustration of a sleeve around the rubber boot after inflation and deflation.

DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1, one of ordinary skill in the art will recognize the typical cross section of an end assembly of an external casing packer (ECP) 10. Within the ECP 10, a mandrel 12 is disposed at the inside diameter of the tool. Radially outwardly of mandrel 12 is an expandable boot/inner-tube 14, which most commonly is constructed of rubber, although other expandable materials may be employed as desired.

Located radially outwardly of boot 14 is an extrusion resistant biaxially woven sleeve 16, which is critical to the functionality of the invention. The sleeve 16 is interposed between the boot 14 and ribs 18 which are mounted within the outer cover 20 and end sleeve 22 of the tool of the invention. Ribs 18 are constructed and overlapped according to industry standards, known to one of ordinary skill in the art. Upon expansion of boot 14, in a noncylindrical shaped borehole environment, ribs 18 expand beyond the intended amount and subject the tool to damage. The distorted ribs 18, even after deflation of the inflatable tool may hinder removal of the tool from the borehole costing both time and money. The interposition of sleeve 16, between boot 14 and ribs 18 provides an effective bridge between

the ribs when they open upon inflation, which is sufficient to retain boot 14 and prevent extrusion thereof through ribs 18. Sleeve 16 is about 18" long and is located substantially over the intersection between end sleeve 22 and rubber outer cover 20 to prevent the deformation of ribs 18 as well as the extrusion of boot 14.

Sleeve 16 may preferably be constructed of carbon fiber or aramid fiber (or kevlar), fiberglass or other similar fiber material having comparable properties. It is noted that the stronger fibers, i.e. carbon, kevlar are preferred.

In construction of the device of the invention referring to figure 3, the uphole end 24 of sleeve 16 is tightly wrapped about hoot 14 and generally does not move from its original location. In order to allow the sleeve 16 to expand however, it is preferable to wrap boot 14 with Teflon tape or other similar friction reducing material under all but the uphole end 24 of sleeve 16. The sleeve 16 is commercially available from A&P Technology, Covington, Kentucky.


Figure 4 illustrates the condition of the sleeve after inflation of boot 14 and deflation thereof. Although damage is notable on the sleeve, it is also apparent that the boot 14 did not extrude through the ribs of the inflatable device. Thus, the construction of the device of the invention overcomes the prior art difficulty of a rubber boot being extruded through the ribs of the inflatable device during inflation in a noncylindrical borehole environment.

4


CLAIMS:

What is claimed is:


- An inflatable tool comprising:
 a mandrel;
 an inflatable element disposed about said mandrel; and
 an extrusion resistant mechanism disposed about said element.
- 2. The inflatable tool of claim 1, wherein said tool further comprises a plurality of ribs disposed about said antiextrusion mechanism.
- 3. The inflatable tool of claim 2, wherein said antiextrusion mechanism is a woven material.
- 4. The inflatable tool of claim 3, wherein said woven material is biaxially woven.
- 5. The inflatable tool of claim 3, wherein said material is one of carbon fiber, Aramid fiber and fiberglass.
- 6. The inflatable tool of claim 1, wherein said tool further includes a friction lowering material disposed between said antiextrusion mechanism and said inflatable element.
- 7. The inflatable tool of claim 6, wherein said friction lowering material is applied to said element.
- 8. The inflatable tool of claim 7, wherein said friction lowering material is Teflon tape.
- 9. The inflatable tool of claim 6, wherein said friction lowering material is applied to said antiextrusion mechanism.
- 10. The inflatable tool of claim 1, wherein said antiextrusion mechanism is composed substantially of material having a low coefficient of friction.




F/G. /



F/G. 2 SUBSTITUTE SHEET (RULE 26)



F/G. 3



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

Interr hal Application No PCT/US 00/19916

A. CLASSII IPC 7	FICATION OF SUBJECT MATTER E21B33/12 E21B33/127							
According to International Patent Classification (IPC) or to both national classification and IPC								
	SEARCHED	33						
Minimum documentation searched (classification system followed by classification symbols) IPC 7 E21B								
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched								
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal								
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT							
Category *	Citation of document, with indication, where appropriate, of the rel	evant passages	Relevant to daim No.					
X	US 4 349 204 A (MALONE BILLY C) 14 September 1982 (1982-09-14)		1,10					
Α	the whole document		5					
X	US 4 745 972 A (CORONADO MARTIN F 24 May 1988 (1988-05-24) abstract; claim 2; figures	P ET AL)	1,2					
Ρ,Χ	US 6 009 951 A (SOLARI MARK C ET 4 January 2000 (2000-01-04) abstract	AL)	1					
A	US 4 979 570 A (MODY RUSTOM K) 25 December 1990 (1990-12-25) the whole document		2-9					
		-/						
			J					
X Furth	er documents are listed in the continuation of box C.	Patent family members are listed	n annex.					
^e Special cat	legories of cited documents :	"T" later document published after the inter	national filing date					
"A" document defining the general state of the art which is not considered to be of particular relevance invention "A" document defining the general state of the art which is not cited to understand the principle or theory underlying the invention								
filing date Accument to particular reverse the unique three most								
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the								
other n	"O" document referring to an oral disclosure, use, exhibition or other means and occument is combined with one or more other such documents, such combination being obvious to a person skilled in the art.							
later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report								
17								
Name and m	nailing address of the ISA	Authorized officer						
	European Patent Office, P.B. 5818 Patentiaan 2 NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Fonseca Fernandez, H						

1

INTERNATIONAL SEARCH REPORT

7

Interr nal Application No PCT/US 00/19916

		PCT/US 00/19916		
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Re	Hevant to claim No.	
A	US 4 632 406 A (AKKERMAN NEIL H) 30 December 1986 (1986-12-30) abstract		1,2,6-9	
Α	US 5 337 823 A (NOBILEAU PHILIPPE C) 16 August 1994 (1994-08-16) figures		3,4	
Α	US 4 852 394 A (GOANS KIP B) 1 August 1989 (1989-08-01) abstract		1	
A	US 3 581 816 A (MALONE BILLY C) 1 June 1971 (1971-06-01)			
Α	US 4 611 658 A (SALERNI JOHN V ET AL) 16 September 1986 (1986-09-16)			
A	US 4 424 861 A (CARTER JR ERNEST E ET AL) 10 January 1984 (1984-01-10)			
!				
:				

1

INTERNATIONAL SEARCH REPORT

...rormation on patent family members

Inter Mal Application No PCT/US 00/19916

Patent document cited in search report	t	Publication date		atent family nember(s)		Publication date
US 4349204	A	14-09-1982	CA GB MX	1176976 2097451 155365	А,В	30-10-1984 03-11-1982 23-02-1988
US 4745972	Α	24-05-1988	NONE			
US 6009951	A	04-01-2000	NONE			
US 4979570	Α	25-12-1990	AU AU BR CA GB NO	625650 6681890 9005813 2029294 2239473 905124	A A A A,B	16-07-1992 06-06-1991 24-09-1991 29-05-1991 03-07-1991 29-05-1991
US 4632406	A	30~12-1986	US CA FR GB GB CA FR GB GB	4477104 1222535 2532713 2126678 2162918 2162919 159450 1177389 2497917 2510703 2091367 2114248	A A,B A,B A,B A A A A A,B	16-10-1984 02-06-1987 09-03-1984 28-03-1984 12-02-1986 12-02-1986 09-06-1989 06-11-1984 16-07-1982 04-02-1983 28-07-1982
US 5337823	A	16-08-1994	FR FR FR AU BR CA DE DE EP WO NO	2662207 2668241 2671787 667661 7962691 9106465 2083156 69130449 0527932 9118180 914136	A B A C D T A A	22-11-1991 24-04-1992 24-07-1992 04-04-1996 10-12-1991 18-05-1993 19-03-1996 10-12-1998 05-08-1999 24-02-1993 28-11-1991 23-04-1992
US 4852394	Α	01-08-1989	NONE			
US 3581816	Α	01-06-1971	NONE			
US 4611658	Α	16-09-1986	NONE			
US 4424861	A	10-01-1984	NONE			